



HDL SERIES

Nureva® HDL310 system

The HDL310 system delivers exceptional audio conferencing without the cost and complexity of a custom pro AV system. It combines a powerful connect module with one integrated microphone and speaker bar to offer advanced processing and premium features for large spaces up to 30' x 30' (9.1 x 9.1 m).

Next-generation microphone pickup

Like all Nureva systems, the HDL310 is powered by patented Microphone Mist™ technology, which fills a space with thousands of virtual mics for true full-room microphone coverage. Because the HDL310's connect module has greater processing power and expanded memory, it unlocks more advanced audio capabilities within the technology — made possible by new algorithms that offer improved echo cancellation, speaker EQ and noise reduction.

Simple wall-mounted installation

Installing the HDL310 is an easy task that takes about 30 minutes. You hang the unit on the wall with two screws, run one cable to the connect module and then another to a computer or other internet-connected device. Compare that to traditional multicomponent systems that may include choosing and installing multiple mics, speakers, cables and a DSP — a process that can take days and require outside technicians.

Tools to set up, manage and customize

The HDL310 includes software and services designed to keep your rooms running smoothly. Nureva Console helps you manage and monitor your devices at scale from a secure, cloud-based platform. The Nureva App makes it simple to set up and configure your HDL310, optimizing the in-room and remote audio experience. The Nureva Developer Toolkit includes cloud-based and local APIs. And every device comes with 2 years of Nureva Pro, which offers expanded support hours, advance hardware replacement and enhanced Nureva Console features.

Features

- **Intelligent Sound Targeting** uses adaptive learning algorithms to preemptively ignore persistent unwanted sounds like HVAC.
- **Position-based gain control** applies gain separately to each sound, which enables specific optimizations that create a natural listening experience.
- **Rapid conversation tracking** quickly switches mic pickup from talker to talker, no matter where they are in the room, so conversations always sound natural.
- **Adaptive Voice Amplification** helps in-room participants hear clearly without diminishing the remote audio experience (audience mute is included).
- **Camera zones** work with sound location data to automatically switch between multiple HDMI and USB cameras.
- **Integrated processing** requires no separate DSP as all processing is integrated into the system.
- **Console Direct** offers a secure, 24/7 network connection to Nureva Console without the need for an in-room PC.



HDL310 system – pro AV performance for rooms up to 30' x 30' (9.1 x 9.1 m)

HDL310

Technology features

Advanced Microphone Mist technology processing platform

Continuous autocalibration

Position-based gain control

Acoustic echo cancellation

Built-in sound masking

Plug and play – no software or drivers required

Ethernet cable to microphone and speaker bar

Primary audio source for video playback

Integrated, multicolor status LED

Microphones

12 low-noise omnidirectional MEMS

Frequency response at 94 dB SPL
100 Hz to 7 kHz

Total harmonic distortion (THD)
0.25% (typical)

Speakers

2 x 20 W 4" aluminum cone

Total harmonic distortion (THD)
0.25% (typical)

Connect module

USB 2.0 interface to computer or collaboration hub, type B

Auxiliary out –
3.5 mm single-ended stereo jack

Auxiliary in –
3.5 mm single-ended stereo jack

2 connections to microphone and speaker bar RJ45

Console Direct RJ45 for connecting to network

Input jack for power supply

Interoperability

Plug and play compatibility with UC&C platforms including Microsoft® Teams, Zoom, Google Meet™, GoTo Meeting, Cisco Webex®, BlueJeans, Lifesize®, RingCentral Meetings™ and more



Easy integration with third-party solutions such as cameras, displays, lecture capture systems, external speakers and headset microphones (for Adaptive Voice Amplification)

Operating

System requirements

Windows® 10 and 11

macOS® 14 and 15
(Sonoma and Sequoia)

Power

Power rating: universal switching
100–240 V AC, 50–60 Hz

Power consumption: <30 W

Environmental

Operating temperature:
0° C to 40° C (32° F to 104° F)

Storage temperature:
-20° C to 70° C (-4° F to 158° F),
humidity 5–90% (noncondensing)

Manageability

Includes Console Direct, which provides a continuous and secure connection to Nureva Console, our cloud-based device management platform

Console Direct security features

Secure IoT OS and system software with device-specific X.509 certificates and external services encrypted using 256-bit Transport Layer Security (TLS)

Information security management system (ISMS) that is ISO/IEC 27001:2022 certified

Built with Microsoft Azure, all data at rest is encrypted using 256-bit AES encryption, and data in transit uses TLS 1.2

Auth0 by Okta for all identity and access management (IAM) services with OAuth 2.0 protocols to identify and authorize users

HDL310 system – pro AV performance for rooms up to 30' x 30' (9.1 x 9.1 m)

Certifications and compatibility

Electromagnetic

FCC Part 15, Class A; ICES-003, Class A;
CISPR 32 (EN 55032), Class A; CISPR 35
(EN 55035); CISPR 24 (EN 55024)

Safety

UL 62368; CAN/CSA-C22.2 NO.62368;
IEC/EN 62368; AS/NZS 62368; UL 60950;
CAN/CSA-C22.2 NO.60950; IEC/EN
60950; AS/NZS 60950

Compliance

RoHS, REACH, POPs (Persistent Organic
Pollutants), WEEE, California Proposition
65, EPA (TSCA – Toxic Substances
Control Act) Restrictions

Dimensions

Integrated microphone and speaker bar

Width: 60.0" (152.4 cm)
Height: 5.91" (14.9 cm)
Depth: 3.5" (9.0 cm)
Weight: 18.0 lb. (8.2 kg)

Connect module

Width: 8.7" (22.2 cm)
Height: 1.46" (3.7 cm)
Depth: 5.91" (15.0 cm)
Weight: 0.97 lb. (0.44 kg)

Shipping

Width: 64.75" (164.4 cm)
Height: 10.63" (27.0 cm)
Depth: 9.5" (24.1 cm)
Weight: 28.0 lb. (12.7 kg)

System includes

Integrated microphone and speaker bar
Connect module, dark gray
Connect module mounting bracket,
dark gray
Country-specific power cable,
6' (2.5 m), black
Ethernet cable, CAT6 SSTP,
50' (15 m), Class 3 rated, black
USB Type A-B cable, 10' (3 m),
VW-1 rated, black
Infrared remote with 2 AAA batteries
Documentation

Warranty

Integrated microphone and
speaker bar and connect module –
standard 2-year limited hardware
Accessories and cables – 30 days
Extended warranty available with
purchase of Nureva Pro extension

Part numbers

Black: **HDL310-B**

White: **HDL310-W**

Nureva Pro extension (1 year): **NP-1Y**

Nureva Pro extension (2 years): **NP-2Y**

Nureva Pro extension (3 years): **NP-3Y**

We are Nureva

We believe that amazing things happen when people come together. They imagine greater possibilities, create better solutions and find greater joy in how they work and learn. It's why we create and support truly original solutions that make it astonishingly easy for our customers to connect and collaborate no matter where they are.

Connect

Nureva Inc.

sales@nureva.com

1.855.568.7382

Book a live demo

Contact sales

© 2026 Nureva Inc. All rights reserved. Nureva, Microphone Mist, the Nureva logo and the Microphone Mist logo are trademarks or registered trademarks of Nureva Inc. in the United States, Canada and other countries. All third-party product and company names are for identification purposes only and may be trademarks of their respective owners. 01/26

